



## **Golden Tee PGA TOUR® Clubhouse Edition Troubleshooting Guide & FAQ\***

### **Troubleshooting Guide**

- 1. The game powers on but there is no boot video on the Main screen or 5-inch touch Monitor on the player control panel.**
  - a. Be sure the HDMI Cable to the Main Monitor is connected to the correct HDMI output on the system box.
  - b. The HDMI EDID Passthrough Emulator must be connected to the Main HDMI output on the system box.
  - c. HDMI Video Cable May be bad. Try another HDM Cable
  - d. The Input on the TV is not selected for the location of the HDMI cable. From the TV Menus select correct Input connection.
  - e. The TV may not be 4K Capable or is Defective
    - i. The TV must be capable of 4K Video Resolution
  - f. The System box may be defective.
- 2. The boot up video displays on the 5" Touch monitor but not the Main Monitor.**
  - a. Make sure The HDMI EDID Emulator is connected to the Main HDMI Video output.
  - b. The Main HDMI video cable is defective.
  - c. If the main TV monitor is not detected the main video will move the display port Video output to the 5" touch monitor.
- 3. No Power up. The fans on the system box do not kick on. No lights on the IO board.**
  - a. Check to be sure the game is getting 110 Volts AC and the power switch on the cabinet is in the on position. If you hear the Bill Validator Cycle and lights on the Bill Validator this indicates AC power is present, and the cabinet Power switch is in the on position.
  - b. Check that the AC Power Cable is connected to the system box and the system box power switch is in the on position.
  - c. The system box may have failed and needs to be repaired or replaced.

\*Please be aware that this guide covers several different product lines, and the information may not all pertain to your device.



### **4. 5-inch Touch Monitor is blank.**

- a. This can happen if the Display port Cable or Micro USB to USB A Cable is unplugged or has a bad connection. This is also caused by a defective 5-inch LCD Monitor.
  - i. Turn off the game and disconnect and reconnect the cables and power back on.
  - ii. Replace the cables with known good cables
  - iii. Replace the 5-inch Touch Monitor.

### **5. 5-inch Monitor “Failed initialization error”.**

- a. This is caused by a bad Micro USB cable, or a Defective 5-inch LCD Monitor.

### **6. Could not find a 4K Resolution Setting on TV, please use a TV/ Monitor that supports 4K.**

- a. A 4K resolution TV is required. This happens when a 1080P or 720P TV is connected to a PGA, 1080P & 720P TVs are NOT supported on PGA Tour.

### **7. Not Connected to IT Net. Error Code: 12? This will happen at the version screen after boot up.**

- a. This indicates the game is not able to connect to the ITNet servers on the network the game is connected to. There can be many reasons why this is happening depending on the type of connection method you are using. See the online troubleshooting information starting on the following page.

### **8. NO BOOTABLE DEVICE error on the main screen at power up.**

- a. Inside the system box the Power cable may be disconnected to the hard drive or the data cable is disconnected.
  - i. Check that the cables are connected
- b. The hard drive in the system box is defective.
  - i. Replace the hard drive

### **9. Prize Play Indicator is Red? The game does not offer prize play.**

- a. The latest Golden Tee PGA TOUR Software year is required.
- b. The latest Patch of the current year is required. The game may need to patch. Patches will be sent to the game automatically.
- c. Game features such as Money Shot, Daily Prizes, Tour Mode may be turned off.
  - i. Enter the games setup menu **SELECT Golden Tee Settings and Audits> Golden Tee Settings.**



### **10. The game will not connect to the network over WiFi selected.**

#### Possible Causes:

- The password is not correct – be sure the password is being entered correctly. Be very aware of upper and lower case
- There may be restrictions on the WiFi Network – if you cell phone or a tablet can connect the game should as well. You may need to contact the network administrator.
- Game WiFi function test – Set your phone up as a hotspot
- Temporarily connect the game to your Cell phone hotspot. If the game can connect to your phone hotspot indicates the games WiFi is functioning. Force a call to further test the connection to the ITNet Servers over your phones hotspot.

### **11. When I scan for a Network, my network is not displayed. There are 10 other networks displayed,**

#### Possible Causes:

- Too Many Networks – The list is limited to 10 networks listed in alphabetical order. Your network name may be too far down the list.
- Solution – Manually add your network. Be aware of upper and lower case. It has to be exact.

### **12. The game indicated it is connected to the locations network but a force call is not successful.**

#### Possible Causes:

- There still may be restrictions on the network. You will need to consult the network administrator. If you smart phone or Tablet can connect to the same network and you can download documents on the network or even surf the internet that game should be able to connect.
- Defective USB WiFi Dongle
- Replace the WiFi Dongle with a known good device.
- Corrupted hard drive. This is very rare.
- Attempt to connect the game over Ethernet. If a game can connect over Ethernet, it should be able to connect on WiFi.
- Replace hard drive – This is a rare occurrence but possible.



### **13. The game does not find the network when connected to Ethernet.**

Possible Causes:

- Bad Ethernet cable
- Not actually connected to a network
- Can another Device Such as a laptop connect to the internet Using the same cable the game is attempting to use.
- The Ethernet cable was connected to the game but never rebooted
- The game will need to power up with an ethernet cable connected. The game will not connect if the cable was connected after the game fully booted up.
- Bad Ethernet port on the Motherboard or corrupted hard drive. These situations are rare but possible.

### **14. The game will not connect to the network over WiFi selected.**

Possible Causes:

- The password is not correct – be sure the password is being entered correctly. Be very aware of upper and lower case
- There may be restrictions on the WiFi Network – if you cell phone or a tablet can connect the game should as well. You may need to contact the network administrator.
- Game WiFi function test – Set your phone up as a hotspot
- Temporarily connect the game to your Cell phone hotspot. If the game can connect to your phone hotspot indicates the games WiFi is functioning. Force a call to further test the connection to the ITNet Servers over your phones hotspot.

### **15. When I scan for a Network, my network is not displayed. There are 10 other networks displayed,**

Possible Causes:

- Too Many Networks – The list is limited to 10 networks listed in alphabetical order. Your network name may be too far down the list.
- Solution – Manually add your network. Be aware of upper and lower case. It has to be exact.



### **16. The game indicated it is connected to the locations network but a force call is not successful.**

Possible Causes:

- There still may be restrictions on the network. You will need to consult the network administrator. If your smart phone or Tablet can connect to the same network and you can download documents on the network or even surf the internet that game should be able to connect.
- Defective USB WiFi Dongle
  - Replace the WiFi Dongle with a known good device. This is the Dongle Part Number and Name: 760365301K WIFI ADAPTER KIT (TITAN). Use this when ordering. Phone Number to place order: 1-847-870-7027 Extension 386. For purchase outside IT: ONLY USE THESE MODELS: Edimax Model EW-7822ULS, ASUS Model USB-AC51.
  - Corrupted hard drive. This is very rare.
  - Attempt to connect the game over Ethernet. If a game can connect
  - Over Ethernet, it should be able to connect on WiFi.
  - Replace hard drive – This is a rare occurrence but possible.

### **17. The game does not find the network when connected to Ethernet.**

Possible Causes:

- Bad Ethernet cable
- Not actually connected to a network
- Can another Device Such as a laptop connect to the internet Using the same cable the game is attempting to use.
- The Ethernet cable was connected to the game but never rebooted. The game will need to power up with an ethernet cable connected.
- The game will not connect if the cable was connected after the game fully booted up.
- Bad Ethernet port on the Motherboard or corrupted hard drive. These situations are rare but possible

### **18. Trackball not functioning in any direction.**

- Trackball is not connected to the I/O board properly. Verify the trackball is connected to J208 labeled Trackball on the I/O Board.
- Defective trackball Interconnect cable. Verify continuity on the trackball Interconnect cable. Repair or replace the cable.
- The I/O Board power Cable from the system box to the I/O board is not connected. Check the 2x2 Connector at the system box and the I/O board.
- The Trackball is defective. Replace the Trackball.
- The IO board is defective. Replace the I/O board. Measure the 5 volts DC to the Trackball. If below 4.5 volts the IO board is likely defective.



### 19. Trackball Works intermittently.

Inside of the trackball is dirty. Clean the Inside of the trackball.

- Rollers are worn. Replace the rollers and bearings.
- Trackball is over-tightened. Do not over-tighten the trackball. Tighten just enough to flatten the lock washers.

### 20. Trouble with the Buttons on the Control Panel.

Use the chart below to diagnose button problems.

#### Buttons

Symptom	Probable Cause	Solution
<b>Button does not work</b>	Switches Common post is not connected to digital ground.	Verify continuity to digital/power supply ground.
	Signal wire is not connected to the Normally Open post of the switch.	Verify continuity from the I/O board to the Normally Open post of the switch.
	The DC power cable from the computer to the I/O board is not connected	Connect the I/O power cable from the Computer to the I/O board. See Appendix D
	Switch is defective	Replace Defective Switch
<b>Button always indicates closed in the player control test. Pressing it will show it is not depressed.</b>	Signal wire is connected to the Normally Closed post of the switch.	Connect signal wire to the Normally Open post of the switch.
<b>Button always indicates closed in player control test even with the switch disconnected entirely.</b>	The DC power cable from the computer to the I/O board is not connected	Connect the I/O power cable from the Computer to the I/O board. See Appendix D
	Defective I/O board	Test on a known good system. Replace if necessary.





## Frequently Asked Questions (FAQ)

### 1. How do you place a game online for players to use Online Features?

#### Online Subscription

To purchase a subscription for online play, please visit our website:

<https://store.itsgames.com/t/games/subscriptions>

If you don't plan to take your game online, it's still important to register. Registration ensures your game is covered under warranty and keeps you in the loop on future updates, enhancements, and important news. Registering your Golden Tee PGA TOUR game ensures you're covered under warranty and stay informed on future updates, enhancements, and important news.

Don't miss out on the latest features and support!

#### Register Your Golden Tee PGA TOUR Game

Get started by registering your game at:

<https://home.itsgames.com/games/golden-tee-pga-tour/registration/new>

#### Online Access

Once subscribed, you can access online features by bringing your GO cabinet online via Dedicated Ethernet or WiFi Adapter.

### 2. How do I connect the game to Wi-Fi?

Enter the setup Menu select **ITNet Settings> Communication Settings Select Configure Wifi.**

- See PGA TOUR Clubhouse Online Configuration Guide on the [Home Owner Resources](#) page of the website.
- A Wifi Dongle Must Be installed. This is the Dongle Part Number and Name: 760365301K WIFI ADAPTER KIT (TITAN). Use this when ordering. Phone Number to place order: 1-847-870-7027 Extension 386. For purchase outside IT: ONLY USE THESE MODELS: Edimax Model EW-7822ULS, ASUS Model USB-AC51.

### 3. How do I get technical service help from Incredible Technologies?

- Know Your game ID number located on the back of the cabinet and on any screen in the service menu in the lower left portion of the screen. Example 14-123456
- Use the Communication form to request help. Select a purpose that best describes your need: <https://amusement.itsgames.com/service>
- 1-800-262-0323 Extension 380 M – F 7 AM to 6 PM Central Standard Time (CST)


### 4. If I want to purchase parts and components, how do I place an order?

- 1-800-262-0323 Extension 386



### 5. What is the Game ID number?

- The game ID is the way the individual game is identified.
- The game ID number is the game serial number, cabinet ID number or cabinet serial number. The terms are interchangeable.
- Example 14-123456
- The game ID number is on the back of the cabinet. This number is also located on the Cabinet Identification Device that is mounted on the left wall inside the cabinet.



**Cabinet Identification Device (CID)**

### 6. What is the purpose of the Cabinet Identification Device, also known as the CID.

- It gives the game an Individual identity. It identifies the Cabinet the game is in.
- It is a product specific component. In this case Golden Tee PGA Tour. It is not course year specific.
- The connection to the system box is a single USB cable. The CID must be connected for the game to operate.
- Do not remove the Cabinet Identification Device from the cabinet. It should only be removed if absolutely necessary. If you move the system box to use it in another Golden Tee PGA Tour cabinet, do not take the CID. The CID should remain in the cabinet it originally has.
- Do not lose the Cabinet Identification Device. It is part of the security of the product and is expensive to replace if lost.





### 7. What is the I/O board?

- a. Input Output board
- b. It reads the buttons and Trackball and communicates that data to the system box through the USB Cable
- c. It is product specific and Course Year Specific. Example: Golden Tee PGA Tour with 2024 courses. If you update a game, the IO board gets updated to the new year version.
- d. It must be connected to the system box for the game to work.
- e. It has a DC Power connection from the System Box to IO board for proper operation. 4 PIN 2X2 Connection at the system box and IO board. Red, Yellow, Black wire cable.

### 8. What is the NFC and what is it used for?

- a. It is used for Player Check in Identification

### 9. How do players use the NFC device for Player Identification Check in

- a. Players can download the Golden Tee PGA TOUR App to their phone. A Link can be found at <https://livewire.itsgames.com/gt/caddy-apps> PGA TOUR requires the PGA Tour App. The Golden Tee Caddy App is for The Golden Tee LIVE Game.
- b. The app holds their NFC Digital Player Card
- c. Follow this hyperlink to How to Use the Golden Tee PGA Tour App: [How to Use GT PGA TOUR App Video](#).

### 10. How do I power my Lighted Marquee on a PGA Tour Showpiece Cabinet.

- a. The showpiece kit has a 2-position connector on the IO power cable that can be used to provide 12 volts and ground to the Marquee light. This can be used if the Marquee light power cable has the matching 2-pin connector. The Marquee has a 2x2 4-pin Power Connector, an adapter is required: This is the Adapter Part Number and Name: 915304214 CABLE ASSY, MARQUEE PWR ADAPTER, TITAN, SHOWPIECE. Use this when ordering. Phone Number to place order: 1- 847-870-7027 Extension 386.

### 11. What is a software patch?

- a. An update to the current Year Version of the game's current software. For many reasons updated software needs to be sent to the game in the form of small patches. The typical size is 2 to 5 Megabytes.



### 12. How does the game get the software patches?

- When a patch is released all games that are connected are sent a random schedule to attempt to receive the patch. At a random time, the game will reset to download the available patch. If it fails, the game will try again 60 minutes after the last patch download started.
- Patches are sent 1 version at a time. If another patch is available, the game will attempt the next patch 60 minutes after the start of the previous patch.

### 13. Can I force the game to receive the patch?

- You are not able to force the game to patch. Make sure the game is online and connected to our servers. The game will attempt the patch typically within an hour.

### 14. Will the game reset to receive a patch while it is being played

- If the game is being played during the time the patch is scheduled, the game will reset as soon as the game is completed. A quick message will be displayed on the game indicating the game will reset to receive the patch.

### 15. What is the EDID Passthrough Emulator?

- This is the device that connects the HDMI output from the system box to the Main monitor. It looks like a Flash Drive.
- This device assures that the main video and audio is sent to the Main monitor. It must be used.
- EDID is an acronym for Extended Display Identification Data
- Golden Tee Go product does not require the EDID Passthrough Emulator



**EDID**



### Technical Problems, Errors or Other Unresolved Issues

If you have lingering technical problems, such as setting up the Ethernet or the WiFi Connection, please visit the Service Department website:

#### [Amusement Technical Services](#)

For more extensive Troubleshooting please call **IT Technical Support at 1-800-262-0323 Ext 380, 7 a.m. – 6 p.m. Monday – Friday.**